Method for generating multiplier coefficients for a mixer

The invention relates to a method for generating
multiplier coefficients for a mixer and to a mixer for
mixing a digital input signal with a sampled sinusoidal
signal.

A modulator has inputs for a carrier quantity and for a
modulating quantity and an output for the signal
produced by the modulation. If modulators are used for
frequency conversion, they are also called mixers or
frequency converters.

Figure 1 shows an arrangement according to the prior
art. A transmit signal generated by a transmitter is
transmitted to a receiver via a transmission channel.
The receiver converts the analog input signal into a
digital signal having a particular frequency f_s. The
mixer performs a frequency conversion by multiplication
in the time domain, in which the sampled signal having
the frequency f_s is downconverted to an intermediate
frequency IF for further data processing. The frequency
conversion takes place at a particular ratio m. In the
case of GSM, for example, m = 10 whereas m = 8 in the
case of wireless LAN.

Figure 2 shows the circuit configuration of a
conventional 1:m mixer according to the prior art. The
sampled signal is applied to an input I of the mixer.
The received digital signal is conducted via data lines
n_i to a multiplier unit which multiplies the received
digital signal by multiplication factors MF_i with a
particular word length WL in the time domain. The
multiplied signal is supplied to a normalizing unit and
output via an output O of the 1:m mixer.

The mixer shown in figure 2 contains a storage device
for storing samples aw_i. In the memory, for example a
ROM, m samples are stored. The samples are cyclically
read out by an address generator and applied to the
5   multiplier unit. The samples aw_i are sampled values of
a sinusoidal signal as shown in figure 3. The example
shown in figure 3 shows the samples which are stored in
a 1:10 mixer according to the prior art. In the memory
of the mixer, 10 samples of the sinusoidal signal aw_0
10   to aw_9 are stored. In the example shown, the stored set
of multipliers is: $MF_i = (0, +MF_1, +MF_2, +MF_2, +MF_1, 0,$
$-MF_1, -MF_2, -MF_2, -MF_1, 0)$.

The mixer according to the prior art, as shown in
15   figure 2, is used for shifting the frequency spectrum
into the baseband of the incoming oversampled received
signal. Mixing is done by the input signal being
multiplied by the sampled sinusoidal signal as shown in
figure 3. The mixing is preferably done after the
20   analog/digital converter as shown in figure 1 since the
signal processing is simpler in the baseband than in
the passband.

In the example shown in figure 3 of a 1:10 mixer,
25   $MF_1 = $ sine $\Pi/5$ and/or   sine   36°   and
$MF_2 = $ sine $2 \Pi/5 = $ sine 72°.

Therefore, $MF_1 = $ sine 36° = 0.587785252...

30   and $MF_2 = $ sine 72° = 0.951056516...

If the amplitude of the received signal with a sampled
sinusoidal signal is quantized, doubling the word
length WL of the signal or sinusoidal signal,
35   respectively, produces an accuracy which is greater by
6 decibels, the increase in accuracy of the ADC/DAC and
of the mixer coefficients is mutually proportional. In
a conventional mixer as shown in figure 2, the word

length WL is increased until the desired accuracy is achieved.

The mixer according to the prior art, shown in figure 2, has the disadvantage that the necessary word length WL is relatively great. This, in turn, has the consequence that the necessary multiplier unit circuit can only be implemented with great complexity. In addition, the storage space for the mixer coefficients, which is necessary for the storage unit, is relatively great.

It is, therefore, the object of the present invention to create a method for generating multiplier coefficients for a mixer and a corresponding mixer in which the word length of the multiplier coefficients is relatively small and which, nevertheless, provide very high accuracy.

According to the invention, this object is achieved by a method having the feature specified in claim 1 and by a mixer having the features specified in claim 8 and 9, respectively.

The invention creates a method for generating multiplier coefficients for a 1:m mixer, comprising the following steps:
recursive calculating of a multiplier set,
selecting a multiplier group, consisting of a number of multipliers, from the calculated multiplier set in dependence on a predetermined signal/noise ratio of the mixer,
and writing multiplier coefficients into a memory of the mixer in accordance with the selected multiplier group.

The method according to the invention leads to multiplier coefficients in which, by doubling the word

length WL of the multiplier coefficients, an accuracy of the mixer is achieved which is higher by 12 dB.

This results in almost perfect mixing, even if the input signals have a low amplitude and/or there are adjacent channels having high amplitudes. As a result, the necessary input word length becomes less. The result is that the area or, respectively, the current consumption of the subsequent stages can also be reduced.

In a preferred embodiment of the method according to the invention, the mixer is a 1:10 mixer, in which, during the recursive calculation, after initialization of a first multiplier V_0 of the multiplier set (MS) to zero ($V_0 = 0$) and

of a second multiplier V_1 of the multiplier set (MS) to one ($V_1 = 1$),

the further multipliers of the multiplier set (MS) are calculated in accordance with the following recursion rule:

$V_{i+2} = V_i + V_{i+1}$ for all $i = 0, 1, 2 \ldots i_{max}$

In a preferred embodiment, a multiplier group consisting of two multipliers is selected from the multiplier, the run index i of which produces a signal/noise ratio

$$(\text{SNR}) = 20\log\left[\frac{1+\sqrt{5}}{2}\right]^2 \cdot \left(i + \frac{1}{2}\right)$$

which is higher than the predetermined signal/noise ratio (SNR_{NOM}) of the mixer.

During this process, the following multiplier coefficients (MC) are preferably written into the memory:

5    $MC = (0, V_i, V_{i+1}, V_{i+1}, V_i, 0, -Vi, -V_{i+1}, -V_{i+1}, V-V_i,)$

In a second embodiment of the 1:10 mixer, a multiplier group consisting of three multipliers is selected from the multiplier set, the run index i of which produces a

10   signal signal/noise ratio $(SNR) = 20\log\left[\dfrac{1+\sqrt{5}}{2}\right]^2 \cdot \left(i + \dfrac{1}{2}\right)$

which is higher than the predetermined signal/noise ratio (SNR_{NOM}) of the mixer.

During this process, the following multiplier
15   coefficients (MC) are preferably written into the memory of the mixer:

$MC = \left(V_i, V_{i+2}, 2{*}V_{1+2}, V_{i+2}, V_1, -V_i, -V_{1+2}, -2{*}V_{1+2}, -V_{i+2}, -V_1\right)$

In an alternative embodiment, the mixer is a 1:8 mixer,
20   in which, during the recursive calculation after initialization
of a first multiplier V_0 of the multiplier set to zero ($V_0 = 0$) and of a second multiplier V_1 of the multiplier set (MS) to one ($V_1 = 1$), the further multipliers of
25   the multiplier set (MS) are calculated in accordance with the following recursion rule:

$V_{i+2} = V_i + V_{i+1}$
$V_{i+3} = V_i + V_{i+2}$

30

for all even-numbered $i = 0, 2, 4 \ldots. i_{max}$

During this process, a multiplier group consisting of two multipliers is selected from the multiplier set,
35   the run index i of which produces a signal/noise ratio

$SNR = 20 \log \left(1 + \sqrt{2}\right) * i$, which is higher than the predetermined signal/noise ratio (SNR_{NOM}) of the mixer.

The following multiplier coefficients (MC) are preferably written into the memory of the mixer:
$MC = (0, V_1, V_{i+1}, V_i, 0, -V_i, -V_{i+1}, -V_1)$

In an alternative embodiment of the 1:8 mixer, a multiplier group (MG) consisting of two multipliers (V_i, V_{i+2}) is selected from the multiplier set (MS), the run index i of which produces a signal/noise ratio $SNR = 20 \log \left[1 + \sqrt{2}\right] (i+1)$ which is higher than the predetermined signal/noise ratio (SNR_{NOM}) of the mixer.

During this process, the following multiplier coefficients (MC) are preferably written into the memory of the mixer:

$MC = (V_i, V_{i+2}, V_{i+2}, V_i, -V_i, -V_{1+2}, -V_{i+2}, -V_i)$

In an alternative embodiment, the mixer is a 1:12 mixer, and during the recursive calculation after initialization of a first multiplier V_0 of the multiplier set (MS) to one ($V_0 = 1$) and of a second multiplier V_1 of the multiplier set (MS) to one ($V_1 = 1$), the further multipliers of the multiplier set (MS) are calculated in accordance with the following recursion rule:

$V_{i+2} = -V_i + 2*V_{i+1}$
$V_{i+3} = V_i + V_{i+1}$
$V_{i+4} = V_i + 2*V_{i+1}$
$V_{i+5} = V_i + 3*V_{i+1}$

During this process, a multiplier group consisting of two multipliers is preferably selected from the multiplier set, the run index i of which produces a

signal/noise ratio SNR $= 20\log\left[\sqrt{2+\sqrt{3}}\right] \cdot (i+2)$ which is higher than the predetermined signal/noise ratio (SNR_{NOM}) of the mixer.

5 The following multiplier coefficients (MC) are preferably written into the memory of the mixer:

$MC = (0, V_i, V_{i+2}, 2*V_i, V_{i+2}, V_i, 0, -V_i, -V_{i+2}, -2*V_i, -2*V_{i+2}, -V_i)$

10

In an alternative embodiment of the 1:12 mixer, a multiplier group consisting of two multipliers (V_{i+3}, V_{i+2}) is selected from the multiplier set (MS), the run index i of which produces a signal/noise ratio

15 SNR $20\log\left[\sqrt{2+\sqrt{3}}\right] \cdot (i+5)$ which is higher than the predetermined signal/noise ratio SNR_{NOM} of the mixer.

During this process, the following multiplier coefficients (MC) are preferably written into the
20 memory of the mixer:

$MC = (V_i, V_{i+3}, V_{i+4}, V_{i+4}, V_{i+3}, V_i, -V_1, -V_{i+3}, -V_{i+4}, -V_{i+4}, -V_{i+3}, -V_i)$

25 The multipliers of the multiplier groups (MG) are preferably resolved into Horner coefficients. Resolving into Horner coefficients provides the possibility of building up the multiplier with simple shift/adder structures. This considerably reduces the circuit
30 complexity for implementing the mixing unit. In addition, it makes it possible to achieve a further saving in storage space in the storage unit.

The invention also creates a mixer for mixing a digital
35 input signal with a sampled sinusoidal signal, comprising

(a)   a multiplier unit for multiplying the digital
       input signal by multiplier coefficients (MC);

5   (b)   and a coefficient memory for storing multiplier
          coefficients (MC) which can be applied to the
          multiplier unit by means of an address generator,

(c)   and comprising a connectable coefficient generator
10   for generating the multiplier coefficients (MC) by
          recursive calculation of a multiplier set (MS)
          from which a multiplier group (MG) consisting of a
          number of multipliers is selected in dependence on
          a predetermined signal/noise ratio (SNR_{NOM}) of the
15   mixer   and   corresponding   multipliers   (MC)   are
          written into the coefficient memory.

The invention also creates a mixer for mixing a digital
input   signal   with   a   sampled   sinusoidal   signal,
20 comprising

(a) a calculation circuit for calculating multipliers
(MC) of a multiplier group (MG), which exhibits a
number of dividing circuits for dividing the digital
25 input signal applied to an input of the mixer, and a
number of switchable adders/subtractors,
- the dividing factors of the dividing circuits being
Horner coefficients of the resolved multipliers (MC) of
the multiplier group (MG),
30 - the adders/subtractors being controlled in dependence
on a first control bit (SUB/ADD) read out of a memory;

(b) a demultiplexer for switching through a zero value
or the multiplier (MC) calculated by the calculating
35 circuit in dependence on a second control bit (zero)
read out of the memory; and comprising

(c) a sign circuit for outputting the positive or negative value switched through by the demultiplexer to an output of the mixer in dependence on a third control bit (SIGN) read out of the memory.

The dividing circuits are preferably shift registers.

In preferred embodiments of the mixer according to the invention, an address generator for reading out the control bits is also provided.

The memory is preferably a read-only memory.

In an alternative embodiment, the memory is programmable.

In the text which follows, preferred embodiments of the method according to the invention for generating multiplier coefficients and of the mixer according to the invention for mixing a digital input signal with a sampled sinusoidal signal are described with reference to the attached figures for explaining features essential to the invention.

In the figures:

figure 1 shows a receiver according to the prior art;

figure 2 shows a 1:m mixer according to the prior art;

figure 3 shows a sampled sinusoidal signal according to the prior art;

figure 4 shows a flow chart for explaining the method according to the invention;

figure 5 shows a block diagram of a first embodiment of the mixer according to the invention;

figure 6 shows a block diagram of a second preferred embodiment of the mixer according to the invention;

5   figure 7 shows a table of the control signals stored in the memory of the mixer shown in figure 6;

figure 8 shows a diagram of the calculated multiplier coefficients in a 1:10 mixer according to the
10 invention.

Figure 4 shows an essential step of the method according to the invention for generating multiplier coefficients for a 1:m mixer according to the
15 invention.

After a start step S_0, after an initialization step for initializing multipliers, multipliers of a multiplier set MS are recursively calculated in a step S_1.
20

Subsequently, a multiplier group MG for a predetermined accuracy is calculated from the calculated multiplier set MS in a step S_2. The predetermined accuracy is obtained from the desired signal/noise ratio SNR_{NOM} of
25 the mixer.

In a further step S_3, the multiplier coefficients are written into the memory of the mixer in accordance with the selected multiplier group MG. The method ends in
30 step S_4.

The method illustrated in figure 4 will be explained by means of an example in the text which follows. By way of example, multiplier coefficients for a 1:10 mixer
35 are calculated in accordance with the method according to the invention.

In step S_1, two multipliers V_0 and V_1 are first initialized in the method according to the invention. During this process, multiplier V_0 is initialized to 0 and the second multiplier V_1 is initialized to 1.

$V_0 = 0; V_1 = 1.$

After that, further multipliers of the multiplier set (MS) are recursively calculated in accordance with the following recursion rule:

$V_{i+2} = V_i + V_{i+1}$ for all $i = 0, 1, 2 \dots i_{max}$

This recursion is a recursion rule for calculating Fibonacci numbers. The resultant multipliers of the multiplier set are:

0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, 89, 144, 233, 377, 610, 987, 1597 ...

From the calculated multiplier set MS specified above, a multiplier group MG consisting of two multipliers V_i, V_{i+1} are selected in accordance with a desired signal/noise ratio SNR of the mixer, the run index i of which produces a signal/noise ratio

$$(SNR) = 20 \log \left[\frac{1+\sqrt{5}}{2} \right]^2 \cdot \left(i + \frac{1}{2} \right) = 8.36 \left(i + \frac{1}{2} \right)$$

which is higher than the predetermined signal/noise ratio SNR_{NOM} of the mixer.

After that, the calculated in-phase multiplier coefficients MC are written into the memory of the mixer:

$MC = (0, Vi, V_{i+1}, V_{i+1}, V_1, 0, -V_i, -V_{i+1}, -V_{i+1}, -V_i)$

In an alternative embodiment of the 1:10 mixer, the multiplier coefficients offset by $\Pi/10$ are calculated instead of the in-phase multiplier coefficients.

5   For this purpose, three multipliers V_i, V_{i+1}, V_{i+2} are selected from the multiplier set MS calculated in step S_1, the run index i of which produces a signal/noise ratio

10    $$(\text{SNR}) = 20\log\left[\frac{1+\sqrt{5}}{2}\right]^2 \cdot (i+1)$$

which is higher than the predetermined signal/noise ratio (SNR_{NOM}) of the mixer.

15   After that, the following multiplier coefficients MC are written into the memory of the mixer in step S_3:

$$\text{MC} = (V_i, \quad V_{i+2}, \quad 2*V_{i+2}, \quad V_{i+2}, \quad V_i, \quad -V_i, \quad -V_{i+2},$$
$$-2*V_{i+2}, -V_{i+2}, \quad -V_i)$$

20

The method according to the invention can also be used for calculating multiplier coefficients for a 1:8 mixer.

25   In this process, a first multiplier V_0 is first initialized to 0 and a second multiplier V_1 of the multiplier set is initialized to 1.

After that, the further multipliers V_i of the
30   multiplier set MS are calculated in accordance with the following recursion rule:

$$V_{i+2} = V_i + V_{i+1}$$
$$V_{i+3} = V_i + V_{i+2}$$

35

Using this recursion rule, the following multipliers of the multiplier set MS are calculated:

0, 1, 1, 1, 2, 3, 5, 7, 12, 17, 29, 41, 70, 99, 169,
5   239, 408, 577, 985, 1393, ...

From the calculated multiplier coefficients MC of the multiplier set (MS), a multiplier group MG consisting of two multipliers V_i, V_{i+1} is selected, the run index
10   i   of   which   produces   a   signal/noise   ratio
$SNR = 20 \log \left(1 + \sqrt{2}\right) * i$ which   is   higher   than   the
predetermined signal/noise ratio (SNR_{NOM}) of the mixer.

In step S_3, the following eight multiplier coefficients
15   (MC) are then written into the memory of the mixer:

$MC = (0, V_i, V_{i+1}, V_i, 0, -V_i, -V_{i+1}, -V_i)$

In   an   alternative   embodiment   for   calculating   the
20   multiplier coefficients in a 1:8 mixer, two multipliers
of V_i, V_{i+1}, which form a multiplier group MG, are
selected from the multiplier set MS, the run index i of
which   produces   a   signal/noise   ratio
$SNR = 20 \log \left(1 + \sqrt{2}\right) (i+1)$ which   is   higher   than   the
25   predetermined signal/noise ratio (SNR_{NOM}) of the mixer.

In step S_3, the following multiplier coefficients MC are then written into the memory of the mixer:

30   $MC = (V_i, V_{i+2}, V_{i+2}, V_i, -V_i, -V_{i+2}, -V_{i+2}, -V_i)$

In   a   further   embodiment   of   the   calculating   method according to the invention for calculating multiplier coefficients, multiplier coefficients for a 1:12 mixer
35   are calculated.

During this process, a first multiplier V_0 is first
initialized to 1 and a second multiplier V_1 is also
initialized to 1.

5   $V_0 = 1$
    $V_1 = 1$

After that, the further multipliers of the multiplier
set MS are calculated in accordance with the following
10   recursion rule:

$V_{i+2} = -V_i + 2*V_{i+1}$
$V_{i+3} = V_i + V_{i+1}$
$V_{i+4} = V_i + 2*V_{i+1}$
15   $V_{i+5} = V_i + 3*V_{i+1}$

The multiplier coefficients calculated in accordance
with this recursion rule are obtained as:

20   1, 1, 2, 3, 4, 5, 7, 11, 15, 19, 26, 41, 56, 71, 97,
    153, 209, 265, 362, 571, 780, 989, 1351, ...

In a step S_2 of the method according to the invention,
a multiplier group MG consisting of two multipliers
25   V_i, V_{i+2} is selected from the multiplier set, the run
index i of which produces a signal/noise ratio
$SNR = 20 \log \left[\sqrt{2 + \sqrt{3}} \right] \cdot (i + 2)$ which is higher
than the predetermined signal/noise ratio (SNR_{NOM}) of
the mixer, where i = 0, 4, 8, ...
30

After that, the following twelve multiplier
coefficients MC are written into the memory of the
mixer in a step S_3:

35   $MC = (0, V_i, V_{i+2}, 2*V_i, V_{i+2}, V_i, 0, -V_i, -V_{i+2}, -2*V_i,$
    $-2*V_{i+2}, -V_i)$ for i = 0, 1, 4, 5, 8, 9 ...

In an alternative embodiment for calculating the multiplier coefficients of the 1:12 mixer, a selection is made from the multiplier set MS for another multiplier group MG consisting of two multipliers V_{i+3},

5   V_{i+4}, the run index i of which produces a signal/noise ratio $SNR = 20\log\left[\sqrt{2 + \sqrt{3}}\right] \cdot (i+5)$ which is higher than the predetermined signal/noise ratio SNR_{NOM} of the mixer, where i = 1, 5, 9 ...

10   The following multiplier coefficients MC are then written into the memory of the mixer in a step S_3:

MC = $(V_i,\ V_{i+3},\ V_{i+4},\ V_{i+4},\ V_{i+3},\ V_i,\ -V_i,\ -V_{i+3},$ $-V_{i+4},\ -V_{i+4},\ -V_{i+3},\ -V_i)$ for i = 1, 3, 5 ...

15

In the examples represented above, multiplier coefficients were calculated for a 1:10, a 1:8 and a 1:12 mixer. With the calculated multiplier coefficients, 1:m mixers according to the invention as

20   shown in figure 5 can be implemented. The example shown in figure 5 is a 1:10 mixer. The mixer 1 according to the invention has a signal input 2 and a signal output 3. The digital input signal converted by the analog/digital converter passes from the input 2 of the

25   mixer 1 via lines 4 to a first input 5 of a multiplier unit 6. The multiplier unit 6 multiplies the digital input signal by stored samples which are supplied to the multiplier unit 6 via lines 7 from a memory 8. The number of lines between a memory 8 and a multiplier

30   unit 6 corresponds to the word length of the memory WL. The multiplier coefficients MM_i read out of the memory 8 are applied to a second input 9 of the multiplier unit 6 via lines 7. The multiplier unit 6 multiplies the digital input value present at input 5 via the

35   sinusoidal output value or multiplier MC_i to form a digital value which is output to a subsequent normalizer 12 via an output 10 of the multiplier unit 6

and lines 11. The normalizer 12 is connected to the output 3 of the mixer 1 according to the invention via lines 13.

5   The memory 8 is enabled by an address generator 15 of the mixer 1 via address lines 14. The address generator 15 cyclically activates the multiplier coefficients MC_i, stored in the memory 8 of the memory unit, for multiplication within the multiplier unit 6.

10

The stored multiplier coefficients MCI can be represented as:

MCI = W_i x 2^k, where $W_i \leq 1$.

15

The normalizing unit 12 following the multiplier unit 6 is provided for normalizing the output value of the multiplier unit 6, the normalizer 12 essentially consisting of a shift register which shifts the output

20 value of the multiplier unit 6 to the right by a certain number of positions.

The memory 8 of the mixer 1 is preferably a read-only memory in which the calculated multiplier coefficients

25 MCI are permanently stored.

In an alternative embodiment, the memory unit 8 is a programmable memory which can be connected to a multiplier coefficient generator 17 via programming

30 lines 16. In the coefficient generator 17, the multiplier coefficients are calculated in accordance with the method according to the invention and are written into the memory 8. For this purpose, the coefficient generator 17 can be preferably supplied

35 with the mixing ratio m and the desired signal/noise ratio SNR_{NOM} for the calculation. The coefficient generator 17 calculates, in dependence on the mixing ratio m = 8, 10, 12 applied and the desired

signal/noise ratio SNR_{NOM} the necessary multiplier coefficients MM_i which are stored in a memory 8.

5 Using the method according to the invention, multiplier coefficients can be calculated in a simple manner for a 1:8, a 1:10 and a 1:12 mixer. During this process, multiplier coefficients MM_i can be calculated in each case for an in-phase set of coefficients and an out-of-phase set of coefficients. The phase shift

10 between a mixer with in-phase set of coefficients and a mixer with out-of-phase set of coefficients is $\Pi/8$, in the case of 1:8 mixer, $\Pi/10$ in the case of a 1:10 mixer and $\Pi/12$ in the case of a 1:12 mixer.

15 According to the invention, mixers having twice the period length, i.e. a 1:16 mixer, a 1:20 mixer and a 1:24 mixer can be implemented in a simple manner by storing both the in-phase set of coefficients and the out-of-phase set of coefficients in the memory 8.

20

In a preferred embodiment of the mixer according to the invention, gain control is also performed following the multiplier unit 6.

25 In the 1:m mixer according to the invention according to the first embodiment as shown in figure 5, the calculated multiplier coefficients MC are distinguished by the fact that they map the sampled sine wave with the greatest possible accuracy with a predetermined

30 word length WL.

Figure 6 shows a particularly preferred embodiment of the mixer 1 according to the invention.

35 In this particularly preferred embodiment, the multiplier unit 6 shown in figure 5 is replaced by a shift register/adder structure so that the circuit

complexity of the mixer 1 according to the invention is greatly reduced.

For this purpose, the multipliers of the multiplier 5 group MG, calculated in accordance with the invention, are split into Horner coefficients.

The Horner dissection is explained by way of example in the text which follows.
10

The embodiment shown in figure 6 is a 1:10 mixer. In the method according to the invention, the multiplier set MS consisting of many multipliers is first calculated in step S_1.
15

After that, two multipliers are selected as multiplier group MG from the calculated multiplier set MS in dependence on a positive signal/noise ratio SNR_{NOM} in step S_2. In the examples shown, for example, 20 multipliers
$V_i = 55$ and
$V_{i+1} = 89$
are selected from the multiplier set MS, which supply the desired signal/noise ratio SNR_{NOM}.
25

The next higher power of 2 of the larger multiplier 89 is 128.

The two multipliers 55, 89 are resolved in accordance 30 with the Horner scheme, as follows:

$$55 : 128 = -1/128 + 1/16 - 1/8 + 1/2 = (((-1/8+1):2-1):4+1):2$$

$$35 \quad 89 : 128 = +1/128 + 1/16 + 1/8 + 1/2 = (((+1/8+1):2+1):4+1):2$$

Figure 6 shows the circuit implementation of the mixer
1 according to the invention for a 1:10 mixer for the
multiplier coefficients 55, 89.

5   The mixer 1 according to the invention contains a
calculating circuit 18 for calculating the multiplier
coefficients MC1 = 55 and MC2 = 89 of the multiplier
group 55, 89. The calculating circuit 18 consists of a
number of dividing circuits 19 - 1, 19 - 2, 19 - 3,
10   19 - 4 and interposed adders/subtractors 20 - 1,
20 - 2, 20 - 3.

The dividing circuits 19 - i are preferably shift
registers which shift the applied digital value to the
15   right by a few bits. In the case of a division by the
factor 8, for example, the digital value applied is
shifted to the right by 3 bits (2^3 = 8). The switchable
adders/subtractors 20 - i add or subtract the applied
values in dependence on a sub/add control signal which
20   is applied to the calculating circuit 18 via a control
line 21. The associated control bit is stored in a
memory 22. In the memory 22 of the second embodiment of
the mixer 1 according to the invention, shown in
figure 6, in contrast to the memory 8 of the first
25   embodiment shown in figure 5, it is not the multiplier
coefficient MC_i itself which is stored but control bits
for generating the multiplier coefficients.

In the example shown in figure 6, the adder/subtractor
30   unit 20 - 1 and the adder/subtractor unit 20/2 are
supplied with the first control bit sub/add, an
addition being performed when the control bit is a
logical 0 and a subtraction being performed when the
control bit is 1.
35

The calculating circuit 8 is followed by a
demultiplexer 23 which receives a zero control bit from
the memory 22 via a further control line 24.

Depending on the received zero control bit, the demultiplexer 23 switches through either the multiplier MC calculated by the calculating circuit 18 or an applied 0. If the zero control bit is zero, the demultiplexer 23 switches through the zero value to a subsequent sign circuit 25. If the zero control bit is logically low, the multiplier value MC calculated by the calculating circuit 18 is conversely switched through to the sign circuit 25 by the demultiplexer 23. The sign circuit 25 consists of an inverting element 26, an adder 27 and a demultiplexer 28 which is activated by a further control bit (SIGN) via a control line 29. The inverting circuit 26 inverts the value output by the demultiplexer 23 which is then added together with a value 1. If the control bit SIGN is a logical 1, the demultiplexer 28 switches the inverted value through to the output of the mixer 1. In the converse case, the non-inverted multiplier coefficient MC_i output by the demultiplexer 28 is output.

Figure 7 shows the memory content of the memory 22 shown in figure 6. In the memory 22, three control bits are in each case stored for each multiplier coefficient MC_i to be calculated of the multiplier coefficient sets MS consisting of ten coefficients so that the memory size is 10 x 3 bits in the example shown. The memory size of the memory 22 is thus considerably less in comparison with the memory size of the mixer according to the first embodiment shown in figure 5 and conventional mixers.

The address generator 15 cyclically generates the memory addresses of the ten registers of the memory 22, in which three control bits are located in each case. The sub/add, zero, SIGN control bits read out activate the calculating circuit 8, the demultiplexer 23 and the sign circuit 25 via control lines 21, 24, 29. At the

output, these generate the two multiplier coefficients 55, 89 and -55, -89, respectively, of the multiplier group.

Figure 8 shows the output of the 1:10 mixer according to the invention, shown in figure 6, for the two multiplier coefficients 55, 89. As can be seen in figure 8, the multiplier coefficients 55, 89 very accurately duplicate a sampled sine wave.

The 1:10 mixer shown in figure 6 exhibits minimum circuit complexity for the calculating circuit 18. In addition, the memory size of the memory 22 can be minimized since only control bits are stored and not the multiplier coefficients MCI themselves.

In the embodiment shown in figure 6, the memory 22 is a ROM memory. In an alternative embodiment, the memory 22 can be programmed via programming lines.